
Università degli Studi di Milano
Master Degree in Computer Science

Information Management course

Teacher: Alberto Ceselli

Lecture 20: 19/12/2012

Data Mining: Concepts and Techniques


(3rd ed.)

— Chapter 10 —

Jiawei Han, Micheline Kamber, and Jian Pei
University of Illinois at Urbana-Champaign &
Simon Fraser University

©2011 Han, Kamber & Pei. All rights reserved.

Cluster Analysis: Basic Concepts and Methods

- Cluster Analysis: Basic Concepts
- Partitioning Methods
- Hierarchical Methods
- Density-Based Methods
- Grid-Based Methods
- Evaluation of Clustering 
- Summary

Assessing Clustering Tendency

- Assess if non-random structure exists in the data by measuring the probability that the data is generated by a uniform data distribution
- Test spatial randomness by statistic test: Hopkins Statistic
 - Given a dataset D regarded as a sample of a random variable o , determine how far away o is from being uniformly distributed in the data space
 - Sample n points, p_1, \dots, p_n , uniformly from the feature space of D . For each p_i , find its nearest neighbor in D : $y_i = \min\{\text{dist}(p_i, v)\}$ where v in D
 - Sample n points, q_1, \dots, q_n , uniformly from D . For each q_i , find its nearest neighbor in $D - \{q_i\}$: $x_i = \min\{\text{dist}(q_i, v)\}$ where v in D and $v \neq q_i$
 - Calculate the Hopkins Statistic:
$$H = \frac{\sum_{i=1}^n y_i}{\sum_{i=1}^n x_i + \sum_{i=1}^n y_i}$$
 - If D is uniformly distributed, $\sum x_i$ and $\sum y_i$ will be close to each other and H is close to 0.5. If D is clustered, H is close to 1

Determine the Number of Clusters

- Empirical method
 - # of clusters $\approx \sqrt{n/2}$ for a dataset of n points
- Elbow method
 - Use the turning point in the curve of sum of within cluster variance w.r.t the # of clusters
- Cross validation method
 - Divide a given data set into m parts
 - Use $m - 1$ parts to obtain a clustering model
 - Use the remaining part to test the quality of the clustering
 - E.g., For each point in the test set, find the closest centroid, and use the sum of squared distance between all points in the test set and the closest centroids to measure how well the model fits the test set
 - For any $k > 0$, repeat it m times, compare the overall quality measure w.r.t. different k 's, and find # of clusters that fits the data the best

Measuring Clustering Quality

- Two methods: extrinsic vs. intrinsic
- Extrinsic: supervised, i.e., the ground truth (ideal clustering, e.g. built by domain experts) is available
 - Compare a clustering against the ground truth using certain clustering quality measure
 - Ex. BCubed precision and recall metrics
- Intrinsic: unsupervised, i.e., the ground truth is unavailable
 - Evaluate the goodness of a clustering by considering how well the clusters are separated, and how compact the clusters are
 - Ex. Silhouette coefficient

Measuring Clustering Quality: Extrinsic Methods


- Clustering quality measure: $Q(C, C_g)$, for a clustering C given the ground truth C_g .
- Q is good if it satisfies the following **4** essential criteria
 - Cluster homogeneity: the purer, the better
 - Cluster completeness: should assign objects belong to the same category in the ground truth to the same cluster
 - Rag bag: putting a heterogeneous object into a pure cluster should be penalized more than putting it into a *rag bag* (i.e., “miscellaneous” or “other” category)
 - Small cluster preservation: splitting a small category into pieces is more harmful than splitting a large category into pieces

Measuring Clustering Quality: Intrinsic Methods

- Silhouette coefficient: similarity metric between objects in the data set
 - Let $C_1 \dots C_k$ be the clusters
 - For each object o in a certain cluster t
 - let $a(o)$ be the average distance between o and the objects of C_t
 - let $b_l(o)$ be the average distance between o and the objects of cluster l ; then $b(o) = \min_{l \neq t} b_l(o)$
- The silhouette coefficient is defined as follows:

$$s(o) = \frac{b(o) - a(o)}{\max(a(o), b(o))}$$

Cluster Analysis: Basic Concepts and Methods

- Cluster Analysis: Basic Concepts
- Partitioning Methods
- Hierarchical Methods
- Density-Based Methods
- Grid-Based Methods
- Evaluation of Clustering
- Summary 

Summary

- **Cluster analysis** groups objects based on their **similarity** and has wide applications
- Measure of similarity can be computed for **various types of data**
- Clustering algorithms can be **categorized** into partitioning methods, hierarchical methods, density-based methods, grid-based methods, and model-based methods
- **K-means** and **K-medoids** algorithms are popular partitioning-based clustering algorithms
- **Birch** and **Chameleon** are interesting hierarchical clustering algorithms, and there are also probabilistic hierarchical clustering algorithms
- **DBSCAN**, **OPTICS**, and **DENCLU** are interesting density-based algorithms
- **STING** and **CLIQUE** are grid-based methods, where **CLIQUE** is also a subspace clustering algorithm
- Quality of clustering results can be evaluated in various ways

References (1)

- R. Agrawal, J. Gehrke, D. Gunopulos, and P. Raghavan. Automatic subspace clustering of high dimensional data for data mining applications. SIGMOD'98
- M. R. Anderberg. Cluster Analysis for Applications. Academic Press, 1973.
- M. Ankerst, M. Breunig, H.-P. Kriegel, and J. Sander. Optics: Ordering points to identify the clustering structure, SIGMOD'99.
- Beil F., Ester M., Xu X.: "Frequent Term-Based Text Clustering", KDD'02
- M. M. Breunig, H.-P. Kriegel, R. Ng, J. Sander. LOF: Identifying Density-Based Local Outliers. SIGMOD 2000.
- M. Ester, H.-P. Kriegel, J. Sander, and X. Xu. A density-based algorithm for discovering clusters in large spatial databases. KDD'96.
- M. Ester, H.-P. Kriegel, and X. Xu. Knowledge discovery in large spatial databases: Focusing techniques for efficient class identification. SSD'95.
- D. Fisher. Knowledge acquisition via incremental conceptual clustering. Machine Learning, 2:139-172, 1987.
- D. Gibson, J. Kleinberg, and P. Raghavan. Clustering categorical data: An approach based on dynamic systems. VLDB'98.

References (2)

- D. Gibson, J. Kleinberg, and P. Raghavan. Clustering categorical data: An approach based on dynamic systems. In Proc. VLDB'98.
- S. Guha, R. Rastogi, and K. Shim. Cure: An efficient clustering algorithm for large databases. SIGMOD'98.
- S. Guha, R. Rastogi, and K. Shim. ROCK: A robust clustering algorithm for categorical attributes. In *ICDE'99*, pp. 512-521, Sydney, Australia, March 1999.
- A. Hinneburg, D. I. A. Keim: An Efficient Approach to Clustering in Large Multimedia Databases with Noise. KDD'98.
- A. K. Jain and R. C. Dubes. Algorithms for Clustering Data. Printice Hall, 1988.
- G. Karypis, E.-H. Han, and V. Kumar. CHAMELEON: A Hierarchical Clustering Algorithm Using Dynamic Modeling. *COMPUTER*, 32(8): 68-75, 1999.
- L. Kaufman and P. J. Rousseeuw. Finding Groups in Data: an Introduction to Cluster Analysis. John Wiley & Sons, 1990.
- E. Knorr and R. Ng. Algorithms for mining distance-based outliers in large datasets. VLDB'98.

References (3)

- G. J. McLachlan and K.E. Bkasford. Mixture Models: Inference and Applications to Clustering. John Wiley and Sons, 1988.
- R. Ng and J. Han. Efficient and effective clustering method for spatial data mining. VLDB'94.
- L. Parsons, E. Haque and H. Liu, Subspace Clustering for High Dimensional Data: A Review, SIGKDD Explorations, 6(1), June 2004
- E. Schikuta. Grid clustering: An efficient hierarchical clustering method for very large data sets. Proc. 1996 Int. Conf. on Pattern Recognition,.
- G. Sheikholeslami, S. Chatterjee, and A. Zhang. WaveCluster: A multi-resolution clustering approach for very large spatial databases. VLDB'98.
- A. K. H. Tung, J. Han, L. V. S. Lakshmanan, and R. T. Ng. Constraint-Based Clustering in Large Databases, ICDT'01.
- A. K. H. Tung, J. Hou, and J. Han. Spatial Clustering in the Presence of Obstacles, ICDE'01
- H. Wang, W. Wang, J. Yang, and P.S. Yu. Clustering by pattern similarity in large data sets, SIGMOD'02.
- W. Wang, Yang, R. Muntz, STING: A Statistical Information grid Approach to Spatial Data Mining, VLDB'97.
- T. Zhang, R. Ramakrishnan, and M. Livny. BIRCH : An efficient data clustering method for very large databases. SIGMOD'96.
- Xiaoxin Yin, Jiawei Han, and Philip Yu, “[LinkClus: Efficient Clustering via Heterogeneous Semantic Links](#)”, in Proc. 2006 Int. Conf. on Very Large Data Bases (VLDB'06), Seoul, Korea, Sept. 2006.