



PyQB

Monga

Gray-Scott
Discrete Laplacian

Programming in Python¹

Mattia Monga

Dip. di Informatica
Università degli Studi di Milano, Italia
mattia.monga@unimi.it

Academic year 2023/24, I semester

¹ © 2023 M. Monga. Creative Commons Attribution — Condividi allo stesso modo 4.0 Internazionale. <http://creativecommons.org/licenses/by-sa/4.0/deed.it>



PyQB

Monga

Gray-Scott
Discrete Laplacian

Lecture XX: Laplacian operator

Gray-Scott systems



PyQB

Monga

Gray-Scott
Discrete Laplacian

Systems driven by the Gray-Scott's equation exhibit **Turing patterns** (D_u, D_v, f, k are constants).

$$\frac{\partial u}{\partial t} = D_u \nabla^2 u - uv^2 + f \cdot (1 - u)$$
$$\frac{\partial v}{\partial t} = D_v \nabla^2 v + uv^2 - (f + k) \cdot v$$

- These give the **change** of u and v chemicals over time
- The diffusion term can be approximated on a grid by computing the discrete Laplacian

Discrete Laplacian



PyQB

Monga

Gray-Scott
Discrete Laplacian

$$\nabla^2 = \nabla \cdot \nabla = \frac{\partial^2}{\partial x^2} + \frac{\partial^2}{\partial y^2}$$

- Change on a grid (1-D):

$$\nabla f[n] = f[n+1] - f[n]$$

$$\nabla f[n] = f[n] - f[n-1]$$

- Second order change (1-D):

$$\begin{aligned} \nabla(\nabla f[n]) &= \nabla(f[n+1]) - \nabla(f[n]) \\ &= (f[n+1] - f[n]) - (f[n] - f[n-1]) \\ &= f[n-1] - 2f[n] + f[n+1] \end{aligned}$$

- In 2-D we do this independently on the 2 dimensions n, m :

$$\begin{aligned} \nabla(\nabla f[n, m]) &= f[n-1, m] - 2f[n, m] + f[n+1, m] + \\ &= f[n, m-1] - 2f[n, m] + f[n, m+1] \\ &= f[n-1, m] + f[n+1, m] + f[n, m-1] + f[n, m+1] - 4f[n, m] \end{aligned}$$

Vectorization



PyQB

Monga

Gray-Scott
Discrete Laplacian

0	0	0	0	0	0
0	13	14	15	16	0
0	9	10	11	12	0
0	5	6	7	8	0
0	1	2	3	4	0
0	0	0	0	0	0

-29	-18	-19	-37
-8	0	0	-13
-4	0	0	9
3	2	1	-5

$X[1:-1, 2:]$ $X[2:, 1:-1]$

$X[1:-1, :-2]$ $X[:-2,$

$1:-1]$ $X[1:-1, 1:-1]$

Same trick we used for "life", but we need to compute the 5-point stencil with these weights (see previous derivation):

0	1	0
1	-4	1
0	1	0

This way one can compute the Laplacian matrix using only vectorized plus.

120



PyQB

Monga

Gray-Scott
Discrete Laplacian

Experimental evidence

Turing proposed his model on a pure theoretical basis, but we have now also some experimental evidence:

Economou, A. D., Ohazama, A., Porntaveetus, T., Sharpe, P. T., Kondo, S., Basson, M. A., Gritli-Linde, A., Cobourne, M. T., Green, J. B. (2012). Periodic stripe formation by a Turing mechanism operating at growth zones in the mammalian palate. Nature genetics, 44(3), 348–351. <https://doi.org/10.1038/ng.1090>

122

Consider also the diagonals



PyQB

Monga

Gray-Scott
Discrete Laplacian

Another approximation which takes into account also the "diagonals" is the 9-point stencil.

1	1	1
1	-8	1
1	1	1

121