



PyQB

Monga

Abstracting similarities

Procedural encapsulation

OO encapsulation

# Programming in Python<sup>1</sup>

Mattia Monga

Dip. di Informatica  
Università degli Studi di Milano, Italia  
mattia.monga@unimi.it

Academic year 2024/25, I semester

<sup>1</sup> © 2024 M. Monga. Creative Commons Attribution — Condividi allo stesso modo 4.0 Internazionale. <http://creativecommons.org/licenses/by-sa/4.0/deed.it>



PyQB

Monga

Abstracting similarities

Procedural encapsulation

OO encapsulation

# Lecture IX: Encapsulation



PyQB

Monga

Abstracting similarities

Procedural encapsulation

OO encapsulation

# State of the homework

	Students	Solved by
One Triangle	20	8
Pythagorean Triplets	15	6
Sonar	9	4
Newton sqrt	5	1
Triangle kinds	5	5
Count chars	5	4



PyQB

Monga

Abstracting similarities

Procedural encapsulation

OO encapsulation

# Procedural abstraction

Procedural abstraction is key for our thinking process (remember the power of recursion, for example): giving a name to a procedure/function enhances our problem solving skills.

```
def sum_range(a: int, b: int) -> int:
    """Sum integers from a through b.

    >>> sum_range(1, 4)
    10

    >>> sum_range(3, 3)
    3
    """
    assert b >= a
    result = 0
    for i in range(a, b+1):
        result = result + i
    return result
```

## Another "sum"



PyQB

Monga

Abstracting similarities

Procedural encapsulation

OO encapsulation

This is very similar...

```
def sum_range_cubes(a: int, b: int) -> int:
    """Sum the cubes of the integers from a through b.

    >>> sum_range_cubes(1, 3)
    36

    >>> sum_range_cubes(-2, 2)
    0

    """
    assert b >= a
    result = 0
    for i in range(a, b+1):
        result = result + cube(i) # cube(i: int) -> int
        ↪ defined elsewhere
    return result
```

63

## Another "sum"



PyQB

Monga

Abstracting similarities

Procedural encapsulation

OO encapsulation

This is also very similar...

$$\frac{1}{a \cdot (a+2)} + \frac{1}{(a+4) \cdot (a+6)} + \frac{1}{(a+8) \cdot (a+10)} + \dots + \frac{1}{(b-2) \cdot (b)}$$

$$\text{(Leibniz: } \frac{1}{1 \cdot 3} + \frac{1}{5 \cdot 7} + \frac{1}{9 \cdot 11} + \dots = \frac{\pi}{8} \text{)}$$

```
def pi_sum(a: int, b: int) -> float:
    """Sum 1/(a(a+2)) terms until (a+2) > b.

    >>> from math import pi
    >>> abs(8*pi_sum(1, 1001) - pi) < 10e-3
    True

    """
    assert b >= a
    result = 0.0
    for i in range(a, b+1, 4):
        result = result + (1 / (i * (i + 2)))
    return result
```

64

## Can we abstract the similarity?



PyQB

Monga

Abstracting similarities

Procedural encapsulation

OO encapsulation

```
from collections.abc import Callable

Num = int | float

def gen_sum(a: int, b: int, fun: Callable[[int], Num], step: int = 1) -> Num:
    """Sum terms from a through b, incrementing by step.

    >>> gen_sum(1, 4, lambda x: x)
    10

    >>> gen_sum(1, 3, lambda x: x**3)
    36

    >>> from math import pi
    >>> abs(8*gen_sum(1, 1000, lambda x: 1 / (x * (x + 2))), 4) - pi < 10e-3
    True

    """
    assert b >= a
    result = 0.0
    for i in range(a, b+1, step):
        result = result + fun(i)
    if isinstance(result, float) and result.is_integer():
        return int(result)
    return result
```

65

## The huge value of procedural abstraction



PyQB

Monga

Abstracting similarities

Procedural encapsulation

OO encapsulation

It is worth to emphasize again the huge value brought by **procedural abstraction**. In Python it is not mandatory to use procedures/functions: the language is designed to be used also for *on the fly* calculations.

```
x = 45
s = 0
for i in range(0, x):
    s = s + i
```

This is ok, but it is not encapsulated (in fact, since encapsulation is so important you can at least consider it encapsulated in file which contains it)

- the piece of functionality is not easily to distinguish

it could be intertwined with other unrelated code

```
x = 45
a = 67 # another concern
s = 0
for i in range(0, x):
    s = s + i
print(a) # another concern
```

- the goal is not explicit, which data are needed, what computes
- it's hard to reuse even in slightly different contexts

66

## Encapsulate the functionality



PyQB

Monga

Abstracting similarities

Procedural encapsulation

OO encapsulation

```
def sum_to(x: int) -> int:
    assert x >= 0
    r = 0
    for i in range(0, x):
        r = r + i
    return r
```

```
s = sum_to(45)
```

- It gives to our mind a “piece of functionality”, the interpreter we are programming is now “able” to do a new thing that can be used **without thinking about the internal details**
- It makes clear which data it needs (an integer,  $\geq 0$  if we add also an assertion or a docstring)
- It makes clear that the interesting result is another integer produced by the calculation
- It can be reused easily and safely

67



PyQB

Monga

Abstracting similarities

Procedural encapsulation

OO encapsulation

## Lecture X: OOP

## Object Oriented encapsulation



PyQB

Monga

Abstracting similarities

Procedural encapsulation

OO encapsulation

Encapsulation is so important that it is used also at a higher level: a collection of related procedures.

```
x = 666
```

```
def increment():
    x = x + 1
```

```
def decrement():
    x = x - 1
```

Again: this is correct Python code, but it has problems:

- Both the functions depends on  $x$  but this is not clear from their signature: a user must look at the internal details
- The two functions cannot be reused individually, but only together with the other (and  $x$ )

69

## Classes



PyQB

Monga

Abstracting similarities

Procedural encapsulation

OO encapsulation

A class is a way to package together a collection of related functions. The class is a “mold” to instance new objects that encapsulated the related functionalities.

```
class Counter:
    def __init__(self, start: int):
        self.x = start

    def increment(self):
        self.x = self.x + 1

    def decrement(self):
        self.x = self.x - 1
```

```
c = Counter(666)
c.decrement()
d = Counter(999)
d.increment()
```

70