Programming in Python[1]

Mattia Monga

Dip. di Informatica
Università degli Studi di Milano, Italia
mattia.monga@unimi.it

Academic year 2025/26, I semester

Lecture VII: Composite objects

Simple and composite objects

- `int`s `float`s `bool`s are simple objects: they have no "parts"
- Strings are an example of composite objects since it is possible to consider also the characters: a `str` is a sequence of single characters; an important (simplifying) property: they are **immutable**
- Generic **immutable** sequences (with elements of any type) are called tuples (`tuple`): `(1, 2, 'foo')` `(1,)`
- Generic **mutable** sequences (with elements of any type) are called lists (`list`): `[1, 2, 'foo']` `[1]` `[1,2].append(3)`

Mutability

Immutable objects are simpler to use:

```
x = (1, 2, 3)
y = x

x = (10, 20, 30) # x refers to a new object, since the
↪  old cannot be changed
print(x, y)
```

Mutable ones require some caution:

```
x = [1, 2, 3]
y = x

x[0] = 10  # both x and y refer to a changed object
print(x, y)

x = [100, 200, 300]
print(x, y)
z = x.copy() # a copy not the same object
```

Exercises

- Write a function `middle(L: list[int]) -> int` which takes a list L as its argument, and returns the item in the middle position of L. (In order that the middle is well-defined, you should assume that L has odd length.) For example, calling `middle([8, 0, 100, 12, 1])` should return 100, since it is positioned exactly in the middle of the list.
  (`assert` is a useful tool to check assumptions — known as preconditions — are indeed true)
- Define a function `prod(L: list[int])` which returns the product of the elements in a list L.

Exercises

https://classroom.github.com/a/Lp1FugLh
https://classroom.github.com/a/lNPDwPcc
https://classroom.github.com/a/Y5qBOvX4